

STANDARD



LRS-35-24



LRS-75-24



LRS-100-24



LRS-150-24



RSP-200-24



RSP-320-24

Código Code	Referência Reference	Alimentação Input	Saída Output	Potência Power	Corrente Current	PFC PFC	DIM DIM	IP IP	Class Class	CxLxA CxLxA	Peso Weight
1000120133	LRS-35-24	85~264VAC + 120~373VDC	24V DC	35W	1.5A		NO	20	I	99*82*30 (mm)	0,23Kg
1000120025	LRS-75-24	85~264VAC + 120~373VDC	24V DC	76,8W	3.2A		NO	20	I	99*97*30 (mm)	0,30Kg
1001002029	LRS-100-24	85~264VAC + 120~373VDC	24V DC	108W	4.5A		NO	20	I	129*97*30 (mm)	0,34Kg
1001001109	LRS-150-24	85~132VAC + 240~370VDC	24V DC	156W	6.5A		NO	20	I	159*97*30 (mm)	0,48Kg
1000120121	RSP-200-24	88~264VAC + 124~370VDC	24V DC	200W	8.4A	PF>0.95	NO	20	I	215*115*30 (mm)	0,72Kg
1000120122	RSP-320-24	88~264VAC + 124~370VDC	24V DC	321.6W	13.4A	PF>0.95	NO	20	I	215*115*30 (mm)	0,90Kg

CALHA DIN | DIN RAILS



DR-30-24



DR-60-24



DR-100-24



NDR-240-24

Código Code	Referência Reference	Alimentação Input	Saída Output	Potência Power	Corrente Current	PFC PFC	DIM DIM	IP IP	Class Class	CxLxA CxLxA	Peso Weight
1000120128	DR-30-24	85~264VAC + 120~370VDC	24V DC	30W	1.5A		NO	20	II	78*93*56 (mm)	0,27Kg
1000120131	DR-60-24	88~264VAC + 124~370VDC	24V DC	60W	2.5A		NO	20	II	78*93*56 (mm)	0,30Kg
1000120130	DR-100-24	88~264VAC + 124~370VDC	24V DC	100W	4.2A		NO	20	II	100*93*56 (mm)	0,35Kg
1000120129	NDR-240-24	90~264VAC + 127~370VDC	24V DC	240W	10A	PF>0.95	NO	20	I	63*125,2*113.5 (mm)	1,00Kg

ESTANQUE | WATERPROOF



LPV-60-24



LPV-100-24



LPV-150-24



ELG-200-24



HLG-320H-24

Código Code	Referência Reference	Alimentação Input	Saída Output	Potência Power	Corrente Current	PFC PFC	DIM DIM	IP IP	Class Class	CxLxA CxLxA	Peso Weight
1000120123	LPV-60-24	90~264VAC + 127~370VDC	24V DC	60W	2.5A		NO	67	II	162,5*42,5*32 (mm)	0,40Kg
1000120124	LPV-100-24	90~264VAC + 127~370VDC	24V DC	100.8W	4.2A		NO	67	II	190*52*37 (mm)	0,63Kg
1000120125	LPV-150-24	180 ~ 305VAC + 254 ~ 431VDC	24V DC	151.2W	6.3A		NO	67	II	191*63*37.5 (mm)	0,74Kg
1000120126	ELG-200-24	100 ~ 305VAC + 142 ~ 431VDC	24V DC	201.6W	8.4A	PF>0.95	NO	65	I	244*71*37.5 (mm)	1,22Kg
1000120127	HLG-320H-24	90 ~ 305VAC + 127 ~ 431VDC	24V DC	320.16W	13,34A	PF>0.95	NO	65	I	252*90*43.8 (mm)	1,88Kg