


A60 STANDARD B22 24V



24V




CODE	WATT (W)	BASE	COLOUR Temp(K)	CRI (Ra)	ANGLE (°)	LUMEN (Lm)	VOLT (Vac/dc)	PF (µF)	FINISH	CLASS	LIFESPAN (h)	DIMENSION		PACKING QTY		
												Ø(mm)	H(mm)	Ind.	Int.	Ext.
0931530017	60	B22	2.700	100	360	980	24	1	Clear	D	1.000	60	105	1	10	100
1181530155	40	B22	2.700	100	360	600	24	1	Frosted	D	1.000	60	105	1	10	100

A60 STANDARD B22 48V 110V



SPECIAL VOLT



CODE	WATT (W)	BASE	COLOUR Temp(K)	CRI (Ra)	ANGLE (°)	LUMEN (Lm)	VOLT (V)	PF (µF)	FINISH	CLASS	LIFESPAN (h)	DIMENSION		PACKING QTY		
												Ø(mm)	H(mm)	Ind.	Int.	Ext.
1181530242	25	B22	2.700	100	360	-	48	1	Clear	E	1.000	60	105	1	10	100
1181530233	40	B22	2.700	100	360	-	110	1	Clear	E	1.000	60	105	1	10	100

INCANDESCENT