



PLL



| CODE | WATT (W) | BASE | COLOUR Temp(K) | CRI (Ra) | ANGLE (°) | LUMEN (Lm) | LAMP Current (A) | PF (µF) | REPLACE Watt (W) | CLASS | LIFESPAN (h) | DIMENSION | | PACKING QTY | | |
|--------------|----------|------|----------------|----------|-----------|------------|------------------|---------|------------------|-------|--------------|-----------|-------|-------------|------|------|
| | | | | | | | | | | | | L(mm) | H(mm) | Ind. | Int. | Ext. |
| 0931510010 | 18 | 2G11 | 2.700 | >80 | 360 | 1.200 | 0,37 | – | 85 | A | 16.000 | 43 | 225 | 1 | 10 | 100 |
| 0931510030 | 18 | 2G11 | 4.200 | >80 | 360 | 1.200 | 0,37 | – | 85 | A | 16.000 | 43 | 225 | 1 | 10 | 100 |
| 0931510049 | 24 | 2G11 | 4.200 | >80 | 360 | 1.800 | 0,34 | – | 121 | A | 16.000 | 43 | 320 | 1 | 10 | 100 |
| 0931510057 | 36 | 2G11 | 2.700 | >80 | 360 | 2.900 | 0,43 | – | 187 | A | 16.000 | 43 | 415 | 1 | 10 | 100 |
| 0931510050CB | 36 | 2G11 | 4.200 | >80 | 360 | 2.900 | 0,43 | – | 187 | A | 16.000 | 43 | 415 | 1 | 10 | 100 |
| 0931510011CB | 55 | 2G11 | 4.200 | >80 | 360 | 4.800 | 0,66 | – | 302 | A+ | 16.000 | 43 | 540 | 1 | 10 | 100 |

PLCI 230V



| CODE | WATT (W) | BASE | COLOUR Temp(K) | CRI (Ra) | ANGLE (°) | LUMEN (Lm) | VOLT (V) | PF (µF) | REPLACE Watt (W) | CLASS | LIFESPAN (h) | DIMENSION | | PACKING QTY | | |
|------------|----------|--------|----------------|----------|-----------|------------|----------|---------|------------------|-------|--------------|-----------|-------|-------------|------|------|
| | | | | | | | | | | | | L(mm) | H(mm) | Ind. | Int. | Ext. |
| 1181510100 | 13 | G24d-1 | 4.000 | >80 | 360 | 900 | 230 | >0,5 | 67 | A | 10.000 | 35 | 140 | 1 | 10 | 50 |

CFLni