


PLC 2P

03



CODE	WATT (W)	BASE	COLOUR Temp(K)	CRI (Ra)	ANGLE (°)	LUMEN (Lm)	LAMP Current (A)	PF (µF)	REPLACE Watt (W)	CLASS	LIFESPAN (h)	DIMENSION		PACKING QTY		
												L(mm)	H(mm)	Ind.	Int.	Ext.
0931510051	10	G24d-1	2.700	>80	360	650	0,21	–	52	A	12.000	35	125	1	10	100
0931510044	10	G24d-1	4.200	>80	360	650	0,21	–	52	A	12.000	35	125	1	10	100
0931510112	13	G24d-1	3.000	>80	360	900	0,21	–	67	A	12.000	35	140	1	10	100
0931510040CB	13	G24d-1	4.200	>80	360	900	0,21	–	67	A	12.000	35	140	1	10	100
0931510048	18	G24d-2	2.700	>80	360	1.300	0,28	–	91	A	12.000	35	155	1	10	100
0931510042CB	18	G24d-2	4.200	>80	360	1.300	0,28	–	91	A	12.000	35	155	1	10	100
0931510055	18	G24d-2	6.500	>80	360	1.300	0,28	–	91	A	12.000	35	155	1	10	100
1181510023	26	G24d-3	2.700	>80	360	1.800	0,42	–	121	A	12.000	35	170	1	10	100
0931510045CB	26	G24d-3	4.200	>80	360	1.800	0,42	–	121	A	12.000	35	170	1	10	100
0931510052	26	G24d-3	6.500	>80	360	1.800	0,42	–	121	A	12.000	35	170	1	10	100



CFLni