


PLCE 4P



CODE	WATT (W)	BASE	COLOUR Temp(K)	CRI (Ra)	ANGLE (°)	LUMEN (Lm)	LAMP Current (A)	PF (µF)	REPLACE Watt (W)	CLASS	LIFESPAN (h)	DIMENSION		PACKING QTY		
												L(mm)	H(mm)	Ind.	Int.	Ext.
0931510056CB	10	G24q-1	4.200	>80	360	650	0,19	–	52	A	12.000	35	115	1	10	100
0931510064CB	13	G24q-1	3.000	>80	360	900	0,17	–	67	A	12.000	35	130	1	10	100
0931510041CB	13	G24q-1	4.200	>80	360	900	0,17	–	67	A	12.000	35	130	1	10	100
0931510120CB	18	G24q-2	3.000	>80	360	1.300	0,22	–	91	A	12.000	35	145	1	10	100
0931510043CB	18	G24q-2	4.200	>80	360	1.300	0,22	–	91	A	12.000	35	145	1	10	100
1401600132	18	G24q-3	6.500	>80	360	1.300	0,22	–	91	A	12.000	35	145	1	10	100
0931510121CB	26	G24q-3	3.000	>80	360	1.800	0,32	–	121	A	12.000	35	160	1	10	100
0931510058CB	26	G24q-3	4.200	>80	360	1.800	0,32	–	121	A	12.000	35	160	1	10	100

