


2D 4P



CODE	WATT (W)	BASE	COLOUR Temp(K)	CRI (Ra)	ANGLE (°)	LUMEN (Lm)	LAMP Current (A)	PF (µF)	REPLACE Watt (W)	CLASS	LIFESPAN (h)	DIMENSION		PACKING QTY		
												L(mm)	H(mm)	Ind.	Int.	Ext.
0931500113CB	16	GR10q	2.700	>80	360	1.050	0,18	–	76	A	10.000	138	141	1	10	40
0931500125B	16	GR10q	4.200	>80	360	1.050	0,18	–	76	A	10.000	138	141	1	10	40
0931500114CB	21	GR10q	2.700	>80	360	1.425	0,24	–	118	A	10.000	138	141	1	10	40
0931500128CB	21	GR10q	4.200	>80	360	1.425	0,24	–	118	A	10.000	138	141	1	10	40
0931500116CB	28	GR10q	2.700	>80	360	2.050	0,32	–	136	A	10.000	205	207	1	10	40
0931500126CB	28	GR10q	4.200	>80	360	2.050	0,32	–	136	A	10.000	205	207	1	10	40
0931500117CB	38	GR10q	2.700	>80	360	2.850	0,34	–	184	A	10.000	205	207	1	10	40
0931500127CB	38	GR10q	4.200	>80	360	2.850	0,34	–	184	A	10.000	205	207	1	10	40
1621500001	55	GR10q	2.700	>80	360	4.050	0,63	–	256	A	10.000	205	207	1	10	40



CFLni