


# T5 FHO



04

CODE	WATT (W)	BASE	COLOUR Temp(K)	CRI (Ra)	ANGLE (°)	LUMEN (Lm)	LAMP Current (A)	PF (µF)	REPLACE Watt (W)	CLASS	LIFESPAN (h)	DIMENSION		PACKING QTY		
												L(mm)	Ø(mm)	Ind.	Int.	Ext.
0931570022	24	G5	3.000	>80	360	1.750	0,29	–	–	A	24.000	549	16	1	25	100
0491570049	24	G5	4.000	>80	360	1.750	0,29	–	–	A	24.000	549	16	1	25	100
0931570029	24	G5	6.500	>80	360	1.750	0,29	–	–	A	24.000	549	16	1	25	100
0931570025	39	G5	3.000	>80	360	3.200	0,32	–	–	A	24.000	849	16	1	25	100
0931570045	39	G5	4.000	>80	360	3.200	0,32	–	–	A	24.000	849	16	1	25	100
0931570053	39	G5	6.500	>80	360	3.200	0,32	–	–	A	24.000	849	16	1	25	100
0931570026	49	G5	3.000	>80	360	4.350	0,25	–	–	A+	24.000	1.449	16	1	25	100
0931570046	49	G5	4.000	>80	360	4.350	0,25	–	–	A+	24.000	1.449	16	1	25	100
0931570180	49	G5	6.500	>80	360	4.350	0,25	–	–	A+	24.000	1.449	16	1	25	100
0931570027	54	G5	3.000	>80	360	4.450	0,45	–	–	A	24.000	1.149	16	1	25	100
0931570047	54	G5	4.000	>80	360	4.450	0,45	–	–	A	24.000	1.149	16	1	25	100
0931570058	54	G5	6.500	>80	360	4.450	0,45	–	–	A	24.000	1.149	16	1	25	100
0931570055	80	G5	3.000	>80	360	6.350	0,53	–	–	A	24.000	1.449	16	1	25	100
0931570056	80	G5	4.000	>80	360	6.350	0,53	–	–	A	24.000	1.449	16	1	25	100
0931570057	80	G5	6.500	>80	360	6.350	0,53	–	–	A	24.000	1.449	16	1	25	100

TF