



**T5 CIRCULAR**



CODE	WATT (W)	BASE	COLOUR Temp(K)	CRI (Ra)	ANGLE (°)	LUMEN (Lm)	LAMP Current (A)	PF (µF)	REPLACE Watt (W)	CLASS	LIFESPAN (h)	DIMENSION		PACKING QTY		
												L(mm)	Ø(mm)	Ind.	Int.	Ext.
0221571018	22	2GX13	3.000	>80	360	1.800	0,3	–	–	A	16.000	225	16	1	10	20
0931570165	22	2GX13	4.200	>80	360	1.800	0,3	–	–	A	16.000	225	16	1	10	20
0931570160	22	2GX13	6.500	>80	360	1.800	0,3	–	–	A	16.000	225	16	1	10	20
0931570166	32	2GX13	4.200	>80	360	2.600	0,3	–	–	A	16.000	270	16	1	10	20
0221571022	40	2GX13	3.000	>80	360	3.200	0,32	–	–	A	16.000	300	16	1	10	20
0221571019	40	2GX13	4.200	>80	360	3.200	0,32	–	–	A	16.000	300	16	1	10	20
0931570162	40	2GX13	6.500	>80	360	3.200	0,32	–	–	A	16.000	300	16	1	10	20
0931570168	40	G10q	6.500	>80	360	3.200	0,32	–	–	A	16.000	300	16	1	10	20
0221571017	55	2GX13	3.000	>80	360	4.200	0,55	–	–	A	16.000	300	16	1	10	20
0221571021	55	2GX13	4.200	>80	360	4.200	0,55	–	–	A	16.000	300	16	1	10	20

**T9 CIRCULAR**



CODE	WATT (W)	BASE	COLOUR Temp(K)	CRI (Ra)	ANGLE (°)	LUMEN (Lm)	LAMP Current (A)	PF (µF)	REPLACE Watt (W)	CLASS	LIFESPAN (h)	DIMENSION		PACKING QTY		
												L(mm)	Ø(mm)	Ind.	Int.	Ext.
0931570090	22	G10q	6.500	>80	360	1.250	0,40	–	–	A	12.000	219	29	1	20	20
0931570091	32	G10q	6.500	>80	360	2.150	0,45	–	–	A	12.000	305	29	1	20	20
0931570092	40	G10q	6.500	>80	360	2.900	0,41	–	–	A	12.000	406	29	1	15	15

TF